



NOTE:

1. CABLE 28AWG(7/0.127 T.C)*25C INSULATION: PVC+DRAIN WIRE+AL/MYLAR+JACKET: PVC COLOR: BEIGE(NK-A03) OD: $\phi 7.0 \pm 0.2$ mm NON-UL
2. CONNECTOR:
 - P1: DB 25P MALE, GOLD FLASH CONTACT, NICKEL PLATED SHELL
 - P2: DB 25F FEMALE, GOLD FLASH CONTACT, NICKEL PLATED SHELL
3. HOOD: MOLDED TYPE, PVC 45P, COLOR: BEIGE(NK-A03)
4. TEST REQUEST:
 - <1>.100% OPEN SHORT & MIS WIRE TEST
 - <2>. INSULATION RESISTANCE 1MΩ MIN
5. PACKING: SEE P-0039 REV.B PACKING DRAWING (BINDING SIZE MUST BE SMALLER THAN BLISTER)

ASSMANN

Electronic GmbH
Auf dem Schüttel 3
58513 Lützenroth

P1	1	2	3	4	5	6	7	8	9	10	11	12	13	14
P2	1	2	3	4	5	6	7	8	9	10	11	12	13	14
	15	16	17	18	19	20	21	22	23	24	25	SHELL		

P/N	EAN CODE NO	DWG NO	LENGTH	PACKING	BLISTER
AK 135 2M	4016032062707	120-5418-1	2000±50mm	(1)	DB VP4
AK 166 3M	4016032062875	120-5418-2	3000±50mm	(1)	DB VP4
AK 136 5M	4016032062714	120-5418-3	5000±100mm	(2)	DB VP5
AK 167 7M		120-5418-4	7000±100mm	(2)	DB VP5
AK 168 10M	4016032062882	120-5418-5	10000±100mm	(2)	DB VP5

Tolerance	Inch	M/M
X	.015	.30
XX	.010	.10
XXX	.005	.05

Title: DB25/M - DB25/F

Customer P/N

App'd

Scale: NENE Units

Dwg No. 120-5418

Rev: C Sheet 1/1

LTR	REV.	DESCRIPTION	DATE
Δ	C	ECN # 010504-4	05/04/01