



**The world will
be connected in
ways humanity
never imagined
possible.**

Aaron McLean



FEATURES

*Easy to access

Front door features a full-length smoked and shatterproof glass door with decorative accent trim reinforced with left/right metal frames and integral locking mechanism.

Side doors; lockable, removable

complete with slam latches and locks.

Rear door; lockable, removable with lock.

Secure, locking front and back doors with spring loaded hinges offer best accessibility even when connecting the cabinets. The door hinge is easily swapped from one side to the other.



All giving you 4-way access to equipment. Front and rear door can be replaced that gives you flexibility for different installations.

*Cable access

Multiple cable entry points provide maximum versatility. There is a rubber edge sliding cover mechanism that protects and fix the cables.

There is a brush on the rear panel that can be positioned on top or bottom (brush entry available on racks of 32U and above)

*Construction

Rigid welded frame construction in steel sheet, rapidly dismantled per 4 screw per corner. Corner of bases have welded sockets on each corner that tightly fixed into the columns gives maximum stability.

Frames are made with 28-fold design for increased stability.

Vented Pagoda-style top cover with built-in space for available top mount cooling system providing protection against dust flow from the top. Besides that it cause a chimney effect to provide passive heat transportation via convection.

19" mounting angles (front/2ea. and back/2ea) allow for flexible configuration and adjustable in depth.

C-rails (3ea.left + 3ea.right) increase the stability of equipment mounting and fixing shelves in 4 points.

Levelling feet is included as a standard feature.

Extensive range of **accessories**.

UNIVERSAL LINE 600x1000

DEPTH = 1000mm.



When ever you need more deeper cabinets for housing networking and server systems...

Depth 1000 cabinets match all features that have defined in the previous pages for UNIVERSAL LINE.



width=600 mm. depth=1000 mm.

Order No.	U (44,45 mm)	h inside height (mm)	H outside height (mm)
CKR 26U6100	26	1184,4	1309,4
CKR 36U6100	36	1629,4	1754,4
CKR 42U6100	42	1896,4	2021,4
CKR 47U6100	47	2118,75	2243,75






Sliding access panel on the bottom for cable entry and a brush entry on the rear panel that can be positioned on the top or bottom




Front door with integrated locking mechanism for added security



△ AVAILABLE IN A STACKABLE CONFIGURATION using our stacking kit



Perforated, vented Pagoda-style top providing maximum protection against dust.



Side panel comes with snap closures and locks providing four-way access to the equipment.