

Mini PS/2 2-port KVM switch with fixed connection cables

Features

- 2-port PS/2 KVM switch
- PS/2 interface power
- High VGA resolution 1920 x 1440
- PS/2 keyboard and mouse control
- LED indicators for easy status monitoring
- Plug-and-play, no driver software needed
- Hotkey control for easy computer selection
- Autoscans mode to browse quickly all connected PCs
- Keyboard/Mouse state saved and restored when switching port
- Support DOS, Windows 3.x/95/98/SE/ME/2000/XP, Unix, Linux
- Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs
- Support Microsoft IntelliMouse®, IntelliMouse Explorer®, Logitech NetMouse® or other compatibles



| | |
|--|---|
| Model No. | 143468 / DC UKV-T02 |
| PC Connections | 2 |
| Console Connections | 1 |
| PC Port Connectors | 2 x PS/2 Keyboard 6-pin Mini Din male 2 x PS/2 Mouse 6 pin Mini Din male 2 x VGA/SVGA HDB 15-pin male |
| Console Port Connectors | 1 x PS/2 Keyboard 6-pin Mini Din female 1 x PS/2 Mouse 6 pin Mini Din female 1x VGA HDB 15 pin female |
| PC selection | Hotkey |
| PC port LED | 2 |
| Scan delay time | 5 ~ 100 sec. programmable (default = 10 sec.) |
| Keyboard/Mouse emulation | PS/2 |
| VGA Resolution | 1920 x 1440 |
| Power Type | PS/2 interface power |
| Operation Temperature | 0 ~ 40° C |
| Storage Temperature | - 20 ~ 60° C |
| Humidity | 0~90% RH, non-condensing |
| Size | Mini |
| Dimension (L x W x H), cable length | 62 × 62 × 26 mm, 1,20m |
| Weight | 160 g |
| Safety / Emission | FCC, CE |