


SPECIFICATION

1. Connector A: LC/PC MM P/N: 11-PM-1-1
2. Connector B: SC/PC MM P/N: 11-HM-1-3
3. Cable Type: Duplex $\varnothing 3.0\text{mm}$ 50/125um MM
4. Length: 2M
5. Jacket Color: Orange
6. Insertion Loss: < 0.5 dB
7. Package: Individual Bag

OPERATION

Fiber Extention: $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
 Ferrule End-face Radius: $10 < R < 25\text{mm}$
 Apex Offset: $< 50\mu\text{m}$
 Increase in insertion loss after 500 mating: 0.2 dB Max.
 Operation Temperature: -20° to $+70^\circ$
 Storage Temperature: -40° to $+80^\circ$
 Humidity (non-condensing) 95%RH

| | | | | | |
|---|-------------------------------|------|-------------|----------|---|
|  | DSGN | MAER | 18.MAY.2004 | ITEM NO: | AL-5LCSC-02I |
| | CHK | | | | |
| UNIT | M / M | APPR | | | Duplex $\varnothing 3.0\text{mm}$ 50/125um MM |
| SCALE | | | | | |
| DWG NO: | ASSMANN Electronic Components | | | | |
| AL-5LCSC-02I | | | | | |