

1

2

3

4

5


6

7

Signature	Revision History	Date	Rev.
Alex.Dan	For Bulk Production	Dec.20,2006	01

A

A



B

B

C

C


D

D

NOTE:

- CABLE:UL2725 [26AWG(1/0.404)×2F INS:HD-PE ID:1.3×2.7+DRAIN WIRE 28AWG(1/0.32)×2C+AL/MY]×2C INNER JACKET:PVC OD:7.3×2.1mm +AL/MY+BRAID(16/10/0.1)PVC JACKET, COLOR: BLACK, OD:9.0×4.0mm, IMPEDANCE: 100 OHM.
- CONNECTOR:
P1&P2:SATA II 7P RIVETING TYPE PBT BLACK G/F W/METAL SHELL
- SHIELD:COPPER-FOIL
- HOOD:MOLDED TYPE, PVC 45P, COLOR:BLACK
- TEST REQUEST:
100% OPEN SHORT MIS WIRE TEST
CONTACT RESISTANCE 3 ohm MAX.
INSULATION RESISTANCE 10M ohm MIN.
HI-POT DC300V/0.01SEC.
- PACKING: SEE P-0039 REV.C PACKING DRAWING.

PIN ASSIGNMENT



E

E

F

F

G

G

H

H

RoHS Compliant

EAN Code:
4016032193845

ST81407

	Date	Name	Part No. AK-ESATA-150
Drawn by	Dec.20,2006	Alex Dan	
Checked by	Dec.20,2006	Norman Xu	
Approved by			

ASSMANN
Electronic GmbH

Title.
External Serial ATA Connectioncable
(eSATA) with metal latch

Scale	N/A	Sheet
Unit	MM	1/1

1

2

3

4

5

6

7